

Rec'd PCT/PTO 09 JUL 2004

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
17 July 2003 (17.07.2003)

PCT

(10) International Publication Number  
**WO 03/057486 A1**

(51) International Patent Classification<sup>7</sup>: **B41F 15/14**,  
15/08, 15/00

(21) International Application Number: PCT/KR03/00046

(22) International Filing Date: 10 January 2003 (10.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
10-2002-0001600 11 January 2002 (11.01.2002) KR

(71) Applicant and

(72) Inventor: **CHOI, Yong-Seok [KR/KR]**; 101-104 Nam-  
suwon-doosan APT, 282 Byeongjeom-ri, Taeae-eup,  
Hwaseong-gun, 445-974 Gyeonggi-do (KR).

(74) Agents: **CHOI, Seog-won et al.**; TAKEWILL Intellectual  
Property Law Office, Rm 1415, Kukje Electronics Center,  
1445-3, Seocho-dong, Seocho-gu, 137-728 SEOUL (KR).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK,  
LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX,  
MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG,  
SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC,  
VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI,  
SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN,  
GQ, GW, ML, MR, NE, SN, TD, TG).

**Declarations under Rule 4.17:**

- as to applicant's entitlement to apply for and be granted a  
patent (Rule 4.17(ii)) for all designations
- of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

(54) Title: METHOD OF SILK SCREEN PRINTING

10

OCTOBER  
2002



(57) Abstract: Disclosed is a method of silk screen printing. The printing method includes coating a diagonal screen made of a screen fabric having a mesh count of 200-300 with a light sensitive emulsion, drying the coated screen, placing a film of 40-60 lines and 60-70 dot percentage on the screen, exposing the screen having the film placed thereon to ultra-violet light for 1-2 min, washing out the screen areas which have not been exposed to the light, and performing screen printing.

WO 03/057486 A1

BEST AVAILABLE COPY